

SHUTTLE CRITICAL ITEMS LIST - ORBITER

SUBSYSTEM : EPD&C - MAIN PROP. FMEA NO 05-6J -2032 -1 REV:06/20/88

ASSEMBLY : APT LCA - 1, 2, 3 CRIT. FUNC: 1R  
 P/N RI : MC477-0261-0002 CRIT. HDW: 3  
 P/N VENDOR:  
 QUANTITY : 6 VEHICLE 102 103 104  
 : SIX EFFECTIVITY: X X X  
 : PHASE(S): PL LO X OO DO LS

REDUNDANCY SCREEN: A-PASS B-FAIL C-PASS  
 PREPARED BY: APPROVED BY: APPROVED BY (NASA):  
 DES *JWB* J BROWN DES *[Signature]* EPDC SSM *[Signature]*  
 REL *[Signature]* DEFENSOR REL *[Signature]* 6/27/88 EPDC REL *[Signature]*  
 QE *[Signature]* D MASAI QE *[Signature]* 6/28/88 MPS REL *[Signature]*

ITEM:

CONTROLLER, HYBRID DRIVER (HDC), TYPE I, GH2/CO2 FLOW CONTROL VALVE (LV53/54/55/56/57/58), RELAY CONTROL POWER.

FUNCTION:

CONDUCTS MAIN BUS POWER TO RELAY FOR SELECTION OF PRIMARY OR STANDBY ULLAGE PRESSURE TRANSDUCER.  
 54V76A121J1(110), J1(113). 55V76A122J1(110), J1(113). 56V76A123J1(110), J1(113).

FAILURE MODE:

LOSS OF OUTPUT, FAILS TO CONDUCT, FAILS TO TURN "ON".

CAUSE(S):

PIECE PART FAILURE, CONTAMINATION, VIBRATION, MECHANICAL SHOCK, PROCESSING ANOMALY, THERMAL STRESS.

EFFECT(S) ON:

(A) SUBSYSTEM (B) INTERFACES (C) MISSION (D) CREW/VEHICLE (E) FUNCTIONAL CRITICALITY

(A) LOSS OF NO. 4 TRANSDUCER CAPABILITY. NO EFFECT UNLESS PRIMARY TRANSDUCER FAILS.

(B,C,D) NO EFFECT - FIRST FAILURE.

SHUTTLE CRITICAL ITEMS LIST - ORBITER

SUBSYSTEM : EPD&C - MAIN PROP. FMEA NO 05-6J -2032 -1 REV:06/20/88

(E) CASE I: LO2/LH2 "LOW" FAILURES.

1R/3, 2 SUCCESS PATHS AFTER FIRST FAILURE.  
TIME FRAME - ASCENT.

- 1) PRELAUNCH, PRIMARY ULLAGE TRANSDUCER FAILS WITH ERRONEOUS LOW OUTPUT AND IS REPLACED WITH NO. 4 TRANSDUCER.
- 2) HDC FAILS "OFF" AFTER LIPTOFF, RETURNING CONTROL OF ASSOCIATED FLOW CONTROL VALVE TO FAULTY PRIMARY TRANSDUCER. VALVE IS COMMANDED OPEN.
- 3) INADVERTENT DEACTUATION OF SECOND FLOW CONTROL VALVE CLOSE SOLENOID.

RESULTS IN EXCESSIVE ULLAGE PRESSURE CAUSING ET VENT VALVE TO RELIEVE EXCESS PRESSURE. POTENTIAL FIRE/EXPLOSION HAZARD EXTERIOR TO THE VEHICLE. POSSIBLE VIOLATION OF THE ET MAXIMUM STRUCTURAL CAPABILITY REQUIREMENTS. POSSIBLE LOSS OF CREW/VEHICLE.

CASE II: LH2 "HIGH" FAILURES.

1R/3, 2 SUCCESS PATHS AFTER FIRST FAILURE.  
TIME FRAME - ASCENT.

- 1) PRELAUNCH, PRIMARY ULLAGE TRANSDUCER FAILS WITH ERRONEOUS HIGH OUTPUT AND IS REPLACED WITH NO. 4 TRANSDUCER.
- 2) HDC FAILS "OFF" AFTER LIPTOFF, RETURNING CONTROL OF ASSOCIATED FLOW CONTROL VALVE TO FAULTY PRIMARY TRANSDUCER. VALVE IS COMMANDED CLOSED.
- 3) INADVERTENT ACTUATION OF SECOND FLOW CONTROL VALVE CLOSE SOLENOID.

RESULTS IN INSUFFICIENT PRESSURIZATION GAS TO MAINTAIN LH2 ULLAGE PRESSURE IN THE REQUIRED FLIGHT CONTROL BAND (32-34 PSIA). POSSIBLE VIOLATION OF TANK MINIMUM STRUCTURAL CAPABILITY REQUIREMENTS AND UNCONTAINED SSME SHUTDOWN DUE TO LOW NPSP. POSSIBLE LOSS OF CREW/VEHICLE.

CASE III: LO2 "HIGH" FAILURES.

1R/3, 2 SUCCESS PATHS AFTER FIRST FAILURE.  
TIME FRAME - ASCENT.

- 1) PRELAUNCH, PRIMARY ULLAGE TRANSDUCER FAILS WITH ERRONEOUS HIGH OUTPUT AND IS REPLACED WITH NO. 4 TRANSDUCER.
- 2) HDC FAILS "OFF" AFTER LIPTOFF, RETURNING CONTROL OF ASSOCIATED FLOW CONTROL VALVE TO FAULTY PRIMARY TRANSDUCER. VALVE IS COMMANDED CLOSED.
- 3) INADVERTENT ACTUATION OF SECOND FLOW CONTROL VALVE CLOSE SOLENOID.

LOSS OF ET LO2 ULLAGE PRESSURE WILL RESULT IN VIOLATION OF TANK MINIMUM STRUCTURAL CAPABILITY REQUIREMENTS. MASS OF LO2 AND VEHICLE ACCELERATION SHOULD BE SUFFICIENT TO MAINTAIN PROPER ENGINE NPSP, DELAYING UNCONTAINED SSME SHUTDOWN DUE TO LOW NPSP UNTIL LATE IN POWERED FLIGHT. POSSIBLE LOSS OF CREW/VEHICLE.

FAILS B SCREEN BECAUSE NO INSTRUMENTATION IS AVAILABLE TO DETECT FAILURE.

05-6J-38

SHUTTLE CRITICAL ITEMS LIST - ORBITER

SUBSYSTEM :EPD&C - MAIN PROP. FMEA NO 05-6J -2032 -1 REV:06/20/88

DISPOSITION & RATIONALE:

(A)DESIGN (B)TEST (C)INSPECTION (D)FAILURE HISTORY (E)OPERATIONAL USE

(A-D) DISPOSITION AND RATIONALE:

REFER TO APPENDIX B, ITEM NO. 1 - HYBRID DRIVER CONTROLLER.

(B) GROUND TURNAROUND TEST

PRESS CNTL REDUNDANCY W/ET SIM V41ACO.030B,D,F; V41ACO.060B,D,F EVERY FLIGHT

(E) OPERATIONAL USE

NO CREW ACTION CAN BE TAKEN FOR LOSS OF GO2 ULLAGE PRESSURE CONTROL OR FAILURES WHICH RESULT IN EXCESSIVE GH2 ULLAGE PRESSURE. THE FOLLOWING ACTIONS CAN BE TAKEN FOR LOW GH2 ULLAGE PRESSURE:

LH2 ULLAGE PRESSURE IS ON SYSTEMS MANAGEMENT (SM) ALERT. CREW WILL OPEN THE LH2 FLOW CONTROL VALVES (VIA COCKPIT SWITCH S53 ON PANEL R2) FOR A LOW LH2 ULLAGE PRESSURE CONDITION.

IF THE LH2 NPSP DROPS BELOW THE PRE-FLIGHT ACCEPTED LEVELS (PER FLIGHT RULES), THE CREW WILL MANUALLY THROTTLE THE ENGINES TO KEEP THE NPSP HIGH ENOUGH TO PREVENT LH2 TURBOPUMP CAVITATION.